



PYRAMEX
Perform At Your Peak™

carhartt

Ironsides® ANSI



RUBBER
NOSEPIECE



RUBBER
TIPS



Straight-back vented, flexible temples

Rubber nosepiece

Rubber temple tips

Available in a Carhartt capture clam or polybag

Capture Clam Part No. **Black and Tan Frame**

CHB618DTCC •	AF	Sandstone Bronze
CHB620DTCC •	AF	Gray
CHB690DTCC •	AF	Antique Mirror

Capture Clam Part No. **Realtree Xtra® Camo Frame**

CHRT618DTCC •	AF	Sandstone Bronze
CHRT620DTCC •	AF	Gray
CHRT690DTCC •	AF	Antique Mirror

Polybag Part No. **Black and Tan Frame**

CHB618DT •	AF	Sandstone Bronze
CHB620DT •	AF	Gray
CHB690DT •	AF	Antique Mirror

Polybag Part No. **Realtree Xtra® Camo Frame**

CHRT618DT •	AF	Sandstone Bronze
CHRT620DT •	AF	Gray
CHRT690DT •	AF	Antique Mirror



Polybags



Capture Clam



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ [•] standards. All lenses provide 99% protection from harmful UV rays and are hard coated polycarbonate scratch-resistant unless otherwise noted.



PYRAMEX
Perform At Your Peak™



Ironside®

General Specifications

Weight: 30.6 gm
 Bridge: 13 mm
 Lens base: 8 curve
 Lens size diagonal: 64 mm
 Lens size vertical: 38 mm
 Lens thickness: 2.0 mm
 Overall length (lens - tip): 130 mm
 Overall width (hinge - hinge): 134 + 1 mm
 Closest point between temple tips: 98 + 5 mm
 Closest point between lens: 15 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Temple: polycarbonate
 Temple tips: thermoplastic rubbers (TPR)
 Screw: stainless steel
 Nosepiece: thermoplastic rubbers (TPR)

Part No.	Frame Marking
CHB618DT	P Z87 + S
CHB618DTCC	P Z87 + S
CHB620DT	P Z87 + S
CHB620DTCC	P Z87 + S
CHB690DT	P Z87 + S
CHB690DTCC	P Z87 + S
CHRT618DT	P Z87 + S
CHRT618DTCC	P Z87 + S
CHRT620DT	P Z87 + S
CHRT620DTCC	P Z87 + S
CHRT690DT	P Z87 + S
CHRT690DTCC	P Z87 + S

Frame Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

S: Special purpose



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967